

Features – Benefits

- **LightStik™** can be inserted into close, confined quarters making inspection easy
- Rechargeable Li-ion battery
- High: 600 lumens, run time 2 hours
Low: 260 lumens, run time 5 hours
Includes 120 lumen light at the end of the light bar
- 5 position tilting detents over an arc of 120 degrees
- Powerful magnetic base, rubber coated to prevent scratching
- Comfortable high grip handle
- Battery charge status indicator
- LED "bulb" is virtually unbreakable and lasts up to 50,000 hours
- Wide base prevents tipping
- Liquid ingress protection: IEC IP54 standard
- Impact resistance: IEC IK07 standard
- Includes 120v charger and USB cable for charging



Order No.
MXN01000

Summary

The WorkStar® **LightStik™** is a rechargeable inspection light and work light designed for daily use in demanding shop environments. The brilliant white flood-style light beam produces a clear, even pattern that is free from hot spots and dark spots. This high performance light produces 600 lumens on high, 260 lumens on low and features a light at the end of the light bar that produces 120 lumens. Run time is from 2 hours to 5 hours depending on light output setting. The powerful magnetic base, is rubber coated to prevent scratching built into the handle. The light bar has 5 positions and tilts through 120 degrees. Includes 120v charger and USB cable.



*Stik Tilts 120° in
5 Steps to Aim Lights*

*Top: 120 lm - narrow beam
Stik: 600 lm - wide beam*

*Wide Base
Won't Tip Over*

*Built-in Powerful
Magnetic Base*

PARAMETER

PERFORMANCE

LED Brightness	High = 600 lumens, Low = 260 lumens, Top: 120 lumens
Power, Color	Main: COB, Daylight White/CRI > 80, 5 W Top: Cree, Daylight White/CRI > 65, 3 W
Main Beam Ratio	The beam diameter to distance ratio is 3:1
Top Beam Ratio	The beam diameter to distance ratio is about 1.5:1
Power/Brightness Switch	Sealed power switch controls top penlight and the 2 brightness levels of the main light
Battery Included	One 18650, 3.7 V, 2.6 Ah Li-ion rechargeable battery, user replaceable
Run Time	High: 2, Low: 5.5, Top: 7 hours
Recharge Time	4 hours
Charge/Discharge Indicator	Three green LEDs arranged in a bar graph format to indicate both the battery life and the charge level
Tilting Head	Head tilts 120 degrees with 5 indented positions
Body Material	ABS plastic with soft rubber grip coating
Magnetic Base	Powerful, rubber coated magnetic base
Dimensions	13.5 x 2.25 x 1.5 inches (34 x 5.5 x 3.8 cm), weight 12 oz (340 g)
Ingress Protection	IP54 = limited dust ingress + water resistant to water jets and rain
Impact/Drop Test	IK07, 6 ft (2 m)
Included	LightStik™ with rechargeable Li-ion battery, 100-220 VAC power supply, USB to micro USB cable